

VP1135A

Single Direction Vibratory Plates



This plate proves that performance is valuable

The VP-Value Plate provides a simple, proven design and high quality construction for confined area soil compaction jobs. A Water tank model provides for excellent results on hot and cold asphalt. The guide handle with vibration damping means longer working hours and less fatigue for the operator.

- Compact design allows for compaction in narrow spaces.
- High travel speeds and easy to maneuver.
- Large capacity water tank and the wide filler opening leads to easy operator use and improved productivity.
- Ergonomically designed lifting handles make loading and unloading from transport vehicles easier for the operator.
- Specially designed exciter bearings reduce maintenance and improve productivity.



Technical specifications

Operating data

| Operating data | |
|---|--|
| Operating weight | 62 kg |
| Centrifugal force | 11 kN |
| Base plate size (w x I) | 350 x 521 mm |
| Operating width | 350 mm |
| Height Lowest working | 640 mm |
| Operating height | 880 mm |
| Frequency | 97 Hz |
| Advance travel (depending on soil) | 25 m/min |
| Advance travel (depending on asphalt) | 28 m/min |
| Surface capacity (depending on soil) | 550 m ² /h |
| Surface capacity (depending on asphalt) | 613 m²/h |
| Engine / Motor | |
| Engine / Motor type | air-cooled single cylinder 4 cycle gasoline engine |
| Engine / Motor manufacturer | Honda |
| Displacement | 118 cm ³ |
| Engine performance | 3 kW |
| at rpm | 3,600 rpm |
| Fuel consumption | 0.8 l/h |
| Tank capacity | 2.5 |
| Power transmission | from drive engine via centrifugal clutch and V-belt directly to exciter which transmits centrifugal force onto baseplate |

^{*}Water tank model available.

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.

Copyright © 2017 Wacker Neuson SE.