

PETROL GENERATORS

Compact, Portable and Maneuverable

THE MOST COMPACT GENERATORS on the market with 15% more power. They can deliver 3 phase and single phase power at the same time. With less than 3% total harmonic distortion they are ideal for high-frequency applications.

CHALLENGE ON THE JOB?

- Having power near to where I am working
- Combining 3 and single phase outlets
- Being easy to move on and off vehicles
- Tight access

SOLUTIONS

- ✓ Most compact portable generator on market
- ✓ Provides dual phase option
- ✓ Handy lifting eye or ramp loadable
- ✓ Easy to position near working area

AVAILABLE MODELS

GEN-10P SPECIFICATIONS

| | |
|------------------|---|
| Max output | 10kVA/8kW |
| Frequency | 50Hz |
| Voltage | 240V/415V |
| Rated output | 6400W |
| Sockets | 2 x 15A single phase + 1 x 20A 3 phase sockets with RCBO protection |
| DRY Weight | 100kgs |
| Noise level (7m) | No load - 72dB 50% load - 76dB 100% load - 78dB |
| Engine | Honda GX-390 |
| Starting system | Pull start |
| Fuel economy | 2.4 L/h @ 50% load |
| Dimensions | 598mm [23in] (L) x 609mm [24in] (W) x 1162mm [46in] (H) |



GEN-16P SPECIFICATIONS

| | |
|------------------|--|
| Max output | 16kVA/19kW |
| Frequency | 50Hz |
| Voltage | 240/415V |
| Rated output | 12,800W |
| Sockets | 2x15A Single Phase or 32A 3-phase sockets with RCBO protection |
| DRY Weight | 155kgs |
| Noise level (7m) | No Load - 72dB 50% Load - 76dB 100% Load - 78dB |
| Engine | GX-690 |
| Starting system | Electric/Key Start |
| Fuel economy | 3.5 L/h @ 50% load |
| Dimensions | 773mm [30in] (L) x 530mm [21in] (W) x 902mm [36in] (H) |



GEN-23P SPECIFICATIONS

| | |
|------------------|--|
| Max output | 23kVA/19kW |
| Frequency | 50Hz |
| Voltage | 240/415V |
| Rated output | 20,00W |
| Sockets | 2x15A Single Phase or 32A 3-phase sockets with RCBO protection |
| DRY Weight | 240kgs |
| Noise level (7m) | 50% Load - 80dB |
| Engine | Vanguard EFI 37hp |
| Starting system | Electric/Key Start |
| Fuel economy | 5.6 L/h @ 50% load |
| Dimensions | 1105mm [43.5in] (L) x 632mm [24.8in] (W) x 1024mm [40.3in] (H) |



GEN-32P SPECIFICATIONS

| | |
|------------------|---|
| Max output | 30kVA |
| Frequency | 50Hz |
| Voltage | 240V/415V |
| Rated output | 24000W |
| Sockets | 2 x 15A single phase + 2 x 32A 3 phase sockets with RCBO protection |
| DRY Weight | 320kgs |
| Noise level (7m) | TBA |
| Engine | Honda GX-690 x 2 |
| Starting system | Electric/Key Start |
| Fuel economy | 10 L/h @ 50% load |
| Dimensions | 1105mm [43.5in] (L) x 632mm [24.8in] (W) x 1206mm [47.4in] (H) |



RFL - permanent magnet alternator

GEN-10P 10Kva



ACCESSORIES

1



1. Rubber feet

2



2. Rubber Handle grips

3



3. Generator Adapter Plug
20A - 32A

4



4. Machine Adapter Plug
with breaker 32A - 20A

Please refer to page 19 for part numbers

Extremely manouverable. We ran a 3 phase grinder, a single phase grinder and a vacuum all at the same time.

Jason, Concrete Artisans

PARALLEL BOX

GEN-10P
&
GEN-16P
WITH
PARALLEL
BOX

