

# FALL PREVENTION EQUIPMENT

## IKAR FLEXIBLE ACCORDING TO EN360:2002

**Housing design:** Plastic or aluminium

**Connective device:** Webbing strap or galvanized steel rope

Sturdy, low-maintenance height-safety device with webbing strap and galvanized steel rope, extra light plastic housing or with aluminium housing and rotational hook suspension. The rotational hook prevents the strap or rope from twisting.

AS/NZS 1891.3 cl 1.6 acknowledges an EN360 listing. Fall Arrest devices complying with EN353-1, EN353-2 or EN360 are acceptable for use in Australia and New Zealand and feature a very high safety standard and worldwide proven technology.

Type Order no.	Connecting Device	Housing	Weight	Dimensions
HWB 2*	2.00 m Web	Aluminium	0.8 kg	240 x 84 x 61
HWB 2,5	2.50 m Web	Aluminium	1.2 kg	315 x 123 x 75
HWB 3,5*	3.50 m Web	Aluminium	1.4 kg	315 x 123 x 75
HWPB 3,5	3.50 m Web	Plastic	1.2 kg	326 x 104 x 78
HWPB 5,5	5.50 m Web	Plastic	1.5 kg	300 x 130 x 78
HWPB 7*	7.00 m Web	Plastic	1.8 kg	300 x 145 x 80
HWPB 9	9.00 m Web	Plastic	2.3 kg	335 x 167 x 88
HWPB 12	12.00 m Web	Plastic	3.4 kg	370 x 195 x 95
HWPB 15*	15.00 m Web	Plastic	4.8 kg	400 x 195 x 95
HWS 4,5	4.50 m Steel rope	Aluminium	2.7 kg	400 x 130 x 78
HWS 6*	6.00 m Steel rope	Aluminium	3.0 kg	400 x 145 x 80
HWS 9*	9.00 m Steel rope	Aluminium	3.7 kg	455 x 160 x 85

\* Stocked items.



SHOCK ABSORBING LANYARDS