

Be Safe.. Think



B-SAFE ANCHOR POINTS (CONT'D)

B-SAFE 316 GRADE STAINLESS STEEL ANCHOR POINTS

Rated at 22kN B-Safe anchor points are designed as permanent purlin mounted anchors. Affording quick and easy installation, B-Safe Anchors are suitable for commercial, industrial and residential applications. It is important to ensure the structure, to which any anchor is installed, has sufficient strength (refer AS/NZS 1891.4) to sustain the applied load.

LOW PROFILE ANCHOR BOLTS

BSC5006MRLP-L

Suitable for large flat pan roof profiles.



BSC5006OLP-L

Suitable for corrugate profiles.



BSC5006LSLP-L

Suitable for long span profiles.



BSL5006A

Angle bracket for timber rafter eyebolt installation.



BSL5000

Temporary roof anchor bracket.



BSL5008

Concrete Anchor 16mm with 150mm thread length (not supplied with chemical).



STANDARD PROFILE ANCHOR BOLTS

BSC5006MR

Suitable for large flat pan roof profiles.



BSC5006O

Suitable for corrugate profiles.



BSC5006LS

Suitable for long span profiles.



BSC5006T

Truss mounted.



BSL5006L

Data plate.



BSL5026

Ladder Access Bracket.



All eyebolts can be colour matched to standard roof colours. Please refer to B-Safe BSC Roof Anchor Installation Instructions for fitting.

A

ANCHORS