Specifications

Model Body color		RTV-X900 General Purpose RTV-X900 W		00 Worksite			RTV-X1100C	RTV-X1140 Worksite	
		Kubota Orange	Kubota	ota Orange Kubota Orange/Realtree® AP (Realtree® AP Camo	Kubota Orange	Kubota Orange	
	Make	KUBOTA	D902-E4-UV		KUBOTA D1105-E4-UV			0 - 0 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
256 1-1	Туре				3-cylinders, 4-	cycle, diesel, OHV		L. N.	
Engine	Displacement cu. in. (cc)	54.	3 (898)		68.	5 (1123)		W213	
	Horsepower HP (kW)/rpm	21.6 (16.1)@3200			24.8 (1	8.5)@3000		~	
	Cooling system		. ,	2222		iquid			
	Battery	54	0 CCA			0 CCA	3 2 2 2 2 3	- 1 T NO	
Transmission				The same of	Variable hydro transmission (VHT-X)			624	
Gear selection			7.7	- Academic -		ard, neutral, reverse			
Max. travelling speed mph (km/h)		0-25 (0-40)				(0-46.4)	0-25 (0-40)		
4WD system	Front differential	2 22 (3 13)		1		lip differential		== (= !=)	
	Rear differential					d differential lock			
Steering						static power	0		-
Front / Rear						isc brakes			
Brakes	Parking brake	The survey	10			, hand operated	A1 Feb 101		
		Name of the last o	4 No. 70 Person 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	- Indeed		, nand operated with adjustable spring pre	alood		
Suspension	Front suspension			maepe	endent, Duar A-arms	205	noau	THE RESERVE AND ADDRESS OF THE PERSON NAMED IN	
	Front suspension travel mm			107-101	landa a a a da ak		The second of	THE RESERVOIS ASSESSMENT OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN THE PERSON NAMED IN COLUMN TWO IS NAMED IN TRANSPORT OF THE PERSON NAMED IN TRANS	- E
	Rear suspension			- Levish	independent (vith coil over shock	12 2 2 3 3 4	The same of the sa	
	Rear suspension travel mm				The second section of	205	465.4	THE RESERVE AND THE PERSON NAMED IN	
Ground clearance	Front mm				266	新元克·米巴·洛兰至人等		285	
	Rear mm	CONTRACTOR OF STREET			263		56.7	240	365 J. H. III
	Under foot platform mm	mm Market Land Control of the Contro		280					
Headlights	THE RESERVE OF THE PROPERTY OF	Two 37.5 watt halogen			Two 37.5 watt blue-tint halogen, optical axis adjustment		Two 37.5 watt halogen		
Occupant Protective System (OPS)	Tubular overhead structure mm	THE RESERVE OF THE PARTY OF THE	11 21 21 21 21		50.8	steel tube		AND DESIGNATION.	1000
	Seat belts	2-point		Total Control	3-point		2-point		
	Certification	SAE J2194 and OSHA 1928 ROPS		I De l	SAE J2194 and OSHA 1928 ROPS and ANSI B71.9		SAE J2194 and OSHA 1928 ROPS		THE 18
Dimensions	Length mm	3055	The second second	The Personal Property lies		3110	AND	3610	THE CL.
	Width mm	OF VALUE OF STREET	100000		605		1660	1605	THE 181
	Height, overall mm	THE RESIDENCE OF THE PARTY OF T	San	2	2020		2090	2025	- TO -
	Front tread centers mm	THE OWN THE STREET STREET	11/2/2011		1240	9/50		1280	TO SELLING
	Rear tread centers mm		THE RESERVE AND ADDRESS OF THE PARTY OF THE		1240	777		1280	100
	Wheelbase mm	The second of th	Colombia 4	4 ()	2045	O. P. C.		2495	
	Turning radius m	TO MAKE AND THE PERSON OF THE	MONEY E TO		4.0	V 0:		5.2	100 110
Weight	kg	865		895	1	935		1075	-
Towing capacity	kg	Land Control of the C		300		590		THE SHALL BUT IN	
Payload capacity	kg	755	N. SCHOOLSFERS	725		685		739	
r dylodd capacity	Material	733		723		Steel		700	-
Cargo bed				1405	1030 × 285	Steel			40F 000 00F
	Width × Length × Depth mm		Contract of the last					Long: 1465 × 1300 × 285 / Short: 14	
	Volume m³				0.43	The second second		Long: 0.54 / Short:	0.28
	Bed height (unloaded) mm		A CONTRACT OF		887			900	
	Cargo bed load kg	AND THE REST OF THE PARTY OF	AND THE REAL PROPERTY.		500			Long: 500 / Short:	300
ETHORES NO	Dumping system	Manual			Hydro	power lift	10		
Fuel tank capacity	ℓ		1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -		20000	30			
Sound rating at oper	ator's ear at max rpm dB. (A)		85			84	83	84	
Tyres	ATV		and the same of the same	- 25)-12, 6-ply			
	HDWS			100	25×10-12, 6-ply				
2 数数数数	TURF			0	25×12-12, 4-ply (N	A RTV-X1100C Camo)		-	
Front guard design		Simple, center only						Centre and bump	per
Alloy wheel			Opt.	4004		Std.		Opt.	
						Std.			

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information. The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires in the table above. Some RTVs in this brochure are shown with optional accessories. For off-highway use only.

Kubota

Kubota Australia Pty Ltd

25-29 Permas Way, Truganina VIC, 3029 Australia Freecall: 1800-334-653 Email: sales@kubota.com.au

Web Site: http://www.kubota.com.au

Kubota New Zealand Limited

Freecall: 0800-582-682 Email: sales@kubota.com.au

Web Site: http://www.kubota.co.nz

Kubota **Genuine Parts** for maximum performance, durability and safety

©2019 Kubota Corporation

RUBOTA 4WD DIESEL UTILITY VEHICLE RUBOTA 4WD DIESEL UTILITY VEHICLE

For Earth, For Life Kubota



The Kubota RTV X-Series. Dependable performance, excellent comfort, all the time.

When there's work to be done on the far side of nowhere, you need a vehicle that can get you there quickly, get the job done efficiently, and get you back comfortably.

RTV-X900

Comfort and versatility make this Kubota's most popular model for all types of jobs. It comes with a powerful 21.6 HP diesel engine and your choice of Kubota Orange or Realtree AP Camo styling.

RTV-X1120D

A step up in power, torque, performance, and style, the RTV-X1120D has everything you need to get the job done, including a rugged and dependable 24.8 HP diesel engine and stylish blue-tinted halogen headlights.

RTV-X1100C

The first RTV to offer a factory-installed unibody A/C cab, the RTV-X1100C is still the industry leader in work comfort. The fully enclosed cab features air conditioning, defroster, and heating systems to keep you comfortable in all types of weather for all types of jobs.

RTV-X1140

When you have cargo to haul, flip up the rear seat and fold down the cargo bed. The RTV-X1140 converts from a 4-passenger vehicle to a 2-passenger RTV with an extra large cargo bed and an industry-leading cargo capacity. A standard hydraulic bed-lift makes short work of dumping tasks.



Power when and where you need it

Even when the path disappears, you can rely on the RTV-X Series' powerful diesel engines to keep you moving forward. Kubota-built and trail-proven, these 3-cylinder liquid-cooled diesel engines have a well-earned reputation for dependable performance even in the harshest terrains. The RTV-X900 comes with a robust 21.6 HP engine, while the RTV-X1120D, RTV-X1100C and RTV-X1140 provide an extra boost of power from 24.8 HP engines.





RTV-X900

VHT-X (Variable Hydraulic Transmission)

Kubota has more experience in variable hydraulic transmissions than any other Utility Vehicle manufacture. The engine torque is maximized through the advanced variable displacement HST motor, resulting in a wider torque band. The Large oil cooler enhances the VHT-X's performance and durability through cooler operating temperatures.



Two-speed In-line Shift

You'll shift less often and maintain better control, thanks to new transmission gearing with just two forward speeds (high and low), plus neutral, and reverse.



Strong High-rigidity Frame

The high-rigidity steel frame isolates the occupants from noise, vibrations, and harshness. With structural strength that few in the industry can match, this durable frame can take years of punishment from heavy loads and rough terrain.

20% Larger, Clogresistant Radiator

Open the hood, and you'll find the radiator and air-intake located high and up front, where the air is cleaner and cooler. This improves both radiator performance and simplifies maintenance. Kubota's wide fin pitch design minimizes clogging, further improving radiator performance.





Get in and buckle up. You're about to experience an advanced level of driving performance.

Front & Rear Extra Duty Independent **I** Suspension



Regardless of the terrain or load, independent suspension on all four wheels ensures a truly exceptional ride. **Kubota's Extra Duty IRS (Independent** Rear Suspension) technology also sets a new standard for durability.





Height-adjustable Front and Rear Suspension

Whether you've got a heavy load or no load at all, adjustment of the front and rear suspension height will ensure the proper vehicle height for a smooth ride and optimum driveability for hard to get to work environments.

High Ground Clearance

The X-series raises the bar on ground clearance—to a full 263 mm with 205 mm of suspension travel—letting you glide over the bumps rather than through them.

Limited-Slip Front Differential


True 4-wheel drive with a limited-slip front differential and a locking rear differential help reduce wheelspin to a minimum, giving you greater control and a smoother ride on rough or muddy terrain.

Multi Wet Disc Brakes/ Dynamic Braking

The RTV-X series uses Multidisc wet brakes which provide longer brake life. You'll also feel more secure, especially when traveling down long inclines, knowing that dynamic braking is providing additional braking power and greater driving control.

CV Joint **Protectors** and **Skid Plates**

Obstacles on the path? CV joint protectors and heavyduty skid plates will protect the most critical parts of the engine and transmission.









60:40 Split-bench Seats

The split-bench style seat is ergonomically designed to provide hours of working comfort. The driver's side is adjustable fore and aft.*

*Drivers side seat adjustment is not available on RTV-X900 General Purpose model & RTV-X1120 models.



Power Steering

Responsive hydrostatic power steering gives you the control you need to tame any terrain. The steering wheel is tilt-adjustable, allowing you to set the optimum angle for your driving style.*

*Tilt-feature is not available on RTV-X900 General Purpose models.



Digital Meter Cluster

Bright, with large, easy-to-read indicators, this digital meter cluster keeps you informed of all critical driving conditions, including speed, hours, and miles traveled. An Overheat Alarm (light and audio) helps prevent engine damage.



Easily accessible Parking Brake

The parking brake is conveniently located on the dashboard for easier access as well as more legroom.



Glove Box*

A large glove box on the passenger side provides fast access to critical tools and personal effects.

*Glove box is not available on RTV-X1100C models.

*Glove box cover is optional on RTV-X900 General Purpose mode



Under-seat Storage Compartments

Large compartments under the split-bench seats provide plenty of convenient storage space for tools, tie-downs, and personal items.



Dumping Cargo Box*

gear secure.

from here to there and back again.
Cargo tie-down hooks help keep your

With the flick of a single lever, the hydraulic-lift cargo box rises and your cargo slides out. Cargo that could take significant physical strength and time to unload can now be dumped with little effort in mere seconds.

*Manual dumping on RTV-X900 General Purpose model.

Spray-on Bed Liner (factory option)

An optional factory-installed bed liner helps protect the cargo bed from dirt and damage. Four tie-down hooks in the corners help keep loads in place.

Towing Capacity

Standard two-inch hitch receivers are located at the front and back. The back receiver lets you tow up to 590 kg of gear.



10

*Photo with factory installed Spray-on Bedliner option.



RTV-X1120D

Three-point Seatbelts

With the RTV-X1120D's increased speed comes increased dynamic loads; so you and your passenger are strapped in with three-point seatbelts.

Half Door

Half doors on the driver and passenger sides help keep out the dirt, brush, and other external objects, while letting you enter and exit with ease.



Alloy Wheels


You'll travel in style with these good-looking, machine-polished alloy wheels.* Clear Coating

helps keep them bright and shiny.

> *Realtree AP Camo model features black alloy wheels with polished outer surfaces.







So comfortable, so fun to drive, you'll find excuses to take it for a spin.

MFORT CAB

RTV-X1100C



Premium Grand Cab

Whether it's hot and humid, cold and windy, or raining cats and dogs, you'll stay dry and comfortable inside the RTV-X1100C's quiet and luxurious air-conditioned and heated cab. Built around a unibody frame that is virtually airtight, soundproof, and rattle-free, the cab incorporates highly efficient air-conditioning, heating, and defogging functions, as well as antennas and speakers for an optional radio. And when the weather is nice? Just roll down the fully opening windows. This truly is the best all-weather, all-comfort, all-the-time working environment you'll ever experience on the trail.



Air Conditioner and Heater

Hot or cold, rain or shine, the temperature inside can always be just right for you. The air conditioner, defroster, and heater system are powerful, efficient, and standard equipment on the RTV-X1100C.





Unibody Cab and Chassis Frame

You'll enjoy a smoother, quieter, more comfortable ride, thanks to the RTV-X1100C's integrated unibody cab and chassis frame. They form a rigid yet lightweight unit that is rugged, airtight, lownoise, and rattle-free. Even more impressive, the cab meets SAE J2194 and OSHA 1928 ROPS standards.





RTV-X1140

From industry-leading cargo capacity to comfortable seating for four adults in three simple steps that can be performed easily by just one person.

[K-vertible™] *Kubota's unique system to convert vehicle from 1 row to 2 row seating less than a minute.*



Reposition the sides of the bed

Swing the front side panels of the cargo bed towards the back of the bed and fold down the front panel.



2 Reposition the cargo bed

Next, lift the front of the cargo bed and secure it.



Reposition the protective screen and bench seat

Next, move back and secure the protective screen with back rest. Finally, lower and secure the bench seat. Reverse these three steps to restore the RTV-X1140's full-length bed.

A variety of standard and optional features to let you work productively and travel comfortably.

RTV-X1140

Newly Designed ROPS

The poles at the rear have been eliminated for a cleaner look and easier cargo loading from the sides in the 2-seat configuration. A 5th pole has been added in the rear middle of the frame to ensure the same high level of ROPS performance that meets the SAE J2194 and OSHA 1928 ROPS standards.



More Comfortable Rear Seat

More legroom for the backseat passengers means more comfort and less fatigue, especially on long journeys. Your crew will arrive fresh and ready for action.



Standard Hydraulic Dump Bed

Dump sand, gravel, turf, or just about anything you can think of, from the RTV-X1140's whopping, 0.54 m²/0.28 m² (two-seat and four-seat configurations, respectively) capacity cargo bed. An easy-to-operate lever activates this hydraulic bed-lift system in either two or four-seat configuration.



