

SITEGUARD TRAILER RANGE – SERIES 5

The Series 5 Trailer Range is designed for frequent relocation between sites, providing seamless mobility. Easily transport surveillance capabilities to any location, ensuring comprehensive coverage without blind spots or lengthy set-up times. The Series 5 systems allow precise placement of monitoring equipment and can be deployed within minutes by anyone. Supplied as a ready-to-use unit, simply tow, deploy and begin monitoring immediately.

SPECIFICATIONS

Mass	Series 5.0: 375kg Series 5.3: 750kg
Compliance	ADR Location Dependent Roadworthy: Yes
Solar Power	415W-440W Solar Panel Combinations (depending on requirements)
Battery Type	Sealed Lead Acid or Lithium Ion Phosphate
Battery Redundancy	Up to 7 Days
Generator & Charger	Option available upon request
Voltage	12V default 24V and 48V available upon request
Trailer Dimensions	Length: 3466mm Width: 1560mm Height (stowed position): 2173mm
Mast Height	Series 5.0: 3.6m Series 5.3: 8.0m
Mast Type	Series 5.0 Aluminium Push Up Mast Series 5.3 Steel Winch Up Mast Pneumatic Option Available Upon Request
Camera Options	Fixed Turret or Bullet Pan Tilt Zoom
Footage Recording	Record to SD card, or option to remote upload to Cloud
Mobile Network	4G
GPS Tracking	Yes
Remote Live-View & Playback	Yes
Material Type	Steel Painted Chassis/Aluminium Body
Operating Temperature	-10°C ~ 60°C
Cable Type	Cat6
Supported Wind	80km/h deployed 120km/h stowed
Supported Headload	Up to 20kg
Custom Branding Available	Yes

